




101433

RING MAXI

Designed by
NAVA + AROSIO

Floodlight for outdoor installation on a façade/wall, with 355° swivel base and allowing horizontal adjustment of +90° / -40°. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium base and head, tempered safety glass, moulded silicone gaskets and o-rings, with screws in stainless steel. Swivel joint with graduated scale and mechanical aiming lock. Built-in LED driver, with 1 COB CREE "CXB 2540" LED. IP68 rating.



light source	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
4000°K neutral-white			
cob led	6/10/14°	5.265	125.36
cob led	20/30/35/40°	5.000	119.05
cob led	55/60/80°	4.770	113.57

Finish color options:



Technical features



Technical data

Wattage	42 WATT
IP Rating	IP68
IK Rating	IK10
Material	High corrosion resistance die-cast copper-free aluminum body
Coating	Polyester powder coating with phosphochromating pre-finish
Light source	1 COB CREE "CXB 2540" LED
Screws	Stainless steel
Transformer	Electronic power supply 100/240V 50/60Hz built-in
Gasket	Silicone rubber
Glass	Tempered
Cable gland	M16 rubber grommet
Power cable	1 mt. power cable included
Gross weight	4,00 Kg
Lamp life	≥ 50000h